

Sandblast Hose (Red)



TECHNICAL SPECIFICATIONS:

APPLICATION	: For conveying abrasive sandblasting materials in cleaning and blasting metal, casting and concrete surfaces
HOSE COLOUR/SURFACE TUBE	: Black/fabric wrapped : Excellent abrasion resistant synthetic rubber *Abrasion resistant: DIN53516 $\leq 60\text{mm}^3$
REINFORCEMENT COVER	: High tensile synthetic fabric with antistatic copper wire : High abrasion and weather resistant synthetic rubber
OPERATING TEMPERATURE	: -20°C to $+80^{\circ}\text{C}$
SAFETY FACTOR	: 3 : 1
PACKAGING	: Coiled and wrapped with transparent PVC film

Part No.	Size	Length	Internal Diameter	External Diameter	Working Pressure		Burst Pressure	
	inch				bar	psi	bar	psi
0032-262/S-N	1	20	25.4	39.0	12	174	36	530
0032-272/S-N	1-1/4	20	32.0	48.0	12	174	36	530
0032-274/S-N	1-1/4	40	32.0	48.0	12	174	36	530

SPEEDO MARINE (PTE) LTD | ADDRESS: 11 TUAS LINK 2, SINGAPORE 638559

TEL: +65 6863 1998 | FAX: +65 6863 1667 | EMAIL: enquiry@speedo.com.sg | WEBSITE: www.speedo.com.sg

Ver. 280920. All written and visual data contained in this document are based on the latest product information available at the time of publication. Speedo Marine (Pte) Ltd reserves the right to make changes at any time without notice. All other brand names or marks are used for identification purposes and are trademarks of their respective owners.